

# Index

- $\Sigma$ - $\Delta$  converters
  - principle, 33
  - (W/L) ratio, 92
  - $\mu$ TAS, 122
  - 4-wire technique, 26
- ABS, 336
- absorption coefficient, 82
- accelerometers, 177
- accuracy, 189
- acoustoelectric effect, 67
- active guarding, 233
- active sensor, 4
- actuators, 62
- advanced chopping, 35
- ambiguous sensor, 11
- angular encoder, 228
  - course measurement, 228, 229
  - precise measurement, 228
- anti-windup controller, 219
- ARM7, 359
- asynchronous converters, 283
- auto-calibration, 243, 282
- avalanche multiplication factor, 110
- backside illumination, 101
- bonding
  - anodic, 133
  - glass-to-glass, 133
  - glass-to-silicon, 133
  - silicon-to-silicon, 133
- braking system, 335
- bridge interface, 45
- bridge interface circuit, 304
- build-in voltage, 95
- burglary alarm, 171
- C high-level programming language, 353
- calibration and trimming, 208
- calorimeter, 178, 214
- cantilever beam, 161
- capacitive sensor, 225
  - circuit configuration, 242
  - interface, 240, 241
  - principles, 226
  - shunting conductances, 240
- capture, 351
- CCD, 69
- central processing unit, 345
- channel-charge injection, 35, 286
- charge coupled device, 69
- chemical sensors, 121
- chopping, 34, 243, 283
  - advanced, 34
- Clark cell, 74
- Clausius-Mossotti factor, 141
- clock and timer system, 346
- clock-feedthrough, 35, 286
- clock module, 349
- clogging, 138
- closed loop sensor system, 5
- color
  - sensor, 113
- condensation, 234

- conduction band, 95
- conductivity gauge, 176
- contamination, 234
- continuity equation, 88
- conversion time, 318
- converters
  - analog-to-digital, 283
  - asynchronous, 283
  - charge-to-time, 286, 300
  - continuous-time, 284
  - duty-cycle-to-digital, 325
  - frequency-to-digital, 315, 331
  - phase-shift-to-digital, 326
  - switched-capacitor (SC), 284
  - time-to-digital, 333
- corroding-free potential, 30
- Coulter counter, 138
- CPU, 345
- cross-effects, 27
- cross-quad capacitor, 229
- cross sensitivity, 190
- cytometers, 135
  
- DACs, 347
- DAQ, 314
- data acquisition, 314
- dead zones, 295
- de-chopping, 34
- Defining Fixed Points, 189
- DEM, 38
  - PTAT voltage source, 206
- DEM switched capacitor amplifier, 39
- DEP, 141
  - sorter, 141
- depletion layer, 94
- detection limit, 103
- detectivity  $D^*$ , 104
- detector
  - absorbing, 79
  - intrinsic, 81
  - photon, 79, 80
  - quantum, 79
  - thermal, 79
- dielectrophoresis
  - effect, 140
  - forces, 141
  - hydrodynamic forces, 140
  - separator, 141
- diffusion coefficient, 88
- diffusion length
  - electron, 98
- digital signal processors, 343
- DIN-IEC 751 standard, 196
- display device, 57
- drift velocity, 92
- DSPs, 343
- duty-cycle-modulated signal, 209, 324
- duty-cycle modulators, 288
- dynamic amplification, 37
- dynamic behavior, 194
- dynamic divider, 40
- dynamic element matching, 38, 206, 283
- dynamic-feedback, 38
- dynamic voltage processing, 306
  
- ear thermometers, 187
- electrical equivalents of thermal parameters,  
157
- electric-field-bending, 231, 232
- electrode configuration
  - condensation, 231, 234
  - contamination, 231, 234
  - electric-field-bending, 231
  - segmented electrodes structures, 234
  - three-layered electrode structure,  
235
- electrolytic conduction, 67
- electronic nose, 130
- electrostatic-field problems, 236
- EM field sensor, 173
- emissivity, 154
- enthalpy, 170
- enzymatic activity, 144
- enzymatic oxidation, 170
- EPROM, 346
- errors
  - multi-path, 34
  - random, 33
  - systematic, 33
- ESD protection, 299
- event managers, 368
- EVs, 368

- excitation signals, 29
  - DC signals, 30
  - pulsed signals, 30
  - sinusoidal, 27
  - square-wave, 30
  - wave shape, 282
  - waveform, 30
- extinction coefficient, 82
- Fabry–Perot interferometer, 115
- field-bending effect, 237
- fine leakage, 26
- floating electrode, 233
- floating membrane, 160
- flow sensors, 174
- FPA, 172
- frequency-to-digital conversion, 316
- front-end circuits, 41
  - capacitive sensors, 43
  - dedicated, 280, 281
  - resistive bridges, 45
  - thermistors, 45
- gain-phase analyzer, 27
- galvanic effect, 67
- geometrical correction factor, 253
- glass-to-glass anodic bonding, 133
- glucose
  - enzymatic oxidation, 170
- glucose oxidase, 170
- gross leakage, 26
- haemoglobin
  - spectra, 127
- Hall
  - coefficient, 252, 255, 260, 276
  - devices, 253
  - effect, 249, 250, 253
  - field, 251
  - mobility, 260
  - voltage, 251
- Hall device
  - biasing, 260
  - horizontal, 256, 258
  - magnetic sensitivity, 260
  - noise, 255
  - nonlinearity, 256
  - offset, 255
  - offset reduction, 260
  - spinning-current technique, 260
  - thermal cross sensitivity, 256
  - vertical, 258
- Hall effect, 67
- Hall probe
  - 3-axis, 270
  - magnetic microscopy, 271
- Hall sensor, 72
- Harvard architecture, 345
- heat leakage, 194
- heat transfer mechanisms, 155
- heating
  - homogeneous, 164
  - resistive, 164
- high-speed screening, 12
- HTS, 144
- humidity sensor, 229
  - capacitive, 227
  - leakage current, 27
- hybrid packages, 66
- hysteresis effects, 190
- impedance, 28
- in situ applications, 126
- incremental sigma–delta A/D con-, 283
- index of refraction, 81
- indirect A/D converter, 294
- industrial revolution, 1
- informatization, 1
- infrared radiation, 154
- infrared sensor, 171, 187
- integrated smart sensor
  - definition, 9
- intelligent transducer
  - definition, 61
- interface
  - resistive sensors, 45
- interrupts, 350
- intrinsic carrier concentration, 88
- ionization coefficient, 110
- IR absorber, 187
- ITO, 90

- JTAG, 374
- laser-induced fluorescence, 145
- leakage current, 105
- learning from nature, 51
- LEDs, 347
- light-emitting diodes, 347
- LIF, 145
- lifetime
  - electron, 98
  - hole, 99
- liquid-level gauge
  - capacitive, 230
- long-term stability, 189
- Lorentz force, 250, 251
  
- MAC module, 345
- magnetic concentrator, 265, 266, 267
- magnetic microscopy, 271
- magnetic sensor system
  - angular position sensor, 267
  - self calibration, 265
- MCUs, 343
- MDC, 316
- mechanization, 1
- membrane structure
  - cantilever beam, 161
  - closed, 163
  - floating, 160
- memory
  - EPROM, 346
  - flash, 346
  - ROM, 346
- MEMS, 101, 165
- metal oxides, 65
- method of the dependent count, 316
- micro total analysis systems, 122
- microcalorimeter, 169
- microcontroller, 343
- microfluidics devices, 131
- micro-Hall sensor, 274
- micro-organisms, 213
  - detection, 29
- mismatching of components, 296
- mobility, 88
- modifier, 56
  
- modulating sensor, 4
- modulation
  - period, 32
  - pulse-width, 32
- modulator
  - capacitive modes, 43
- module
  - output-compare, 354
- multi-path errors, 33
- multi-path signals, 30
- multiple-electrode capacitive sensors, 237
- multiplexed sensing elements, 295
- multiply-and-accumulate, 345
  
- NADH, 144
- nanocalorimeter, 177
- NEP, 106
- Nernst effect, 67
- nested-chopper technique, 35
- noise and resolution, 190
  
- Object-Oriented Design, 24
- oil-condition monitoring
  - viscosity-permittivity, 129
- oil deterioration
  - infrared measurement, 130
- one-time-programming capability, 346
- open loop sensor system, 5
- optical
  - sensor, 79
- optical glass fibers, 66
- optical microspectrometer, 115
- OTP, 346
- output-compare, 354
- oximeter, 127
- oxyhaemoglobin
  - spectra, 127
  
- packaging
  - compatibility, 25
- parasitic capacitance effect, 239
- particle-shape sensor, 135
- passive sensor, 4
- period-modulated signal, 31
- period modulation, 290

- peripherals, 350
  - analog, 347
  - digital, 346
- personal detector, 233
- PGA, 372
- phase transition, 154
- phonon, 83
- photoconductive gain, 92
- photoconductor, 88, 89
- photodiode, 88
  - avalanche, 109
  - PIN, 100
  - stacked, 102
- photon flux, 83
- phototransistor, 109
- photovoltaic effect, 67
- physical chemosensor, 74
- physical chemosensors
  - definition, 123
  - electrical principles, 126
  - energy domains, 125
  - magnetic principles, 126
  - mechanical principles, 125
  - optical principles, 124
  - thermal principles, 125
- piezoelectricity
  - effect, 65
  - materials, 65
  - polymers, 65
- piezoresistivity
  - pressure sensor, 70
- Pirani gauges, 154
- platinum (Pt) resistance thermometer, 189
  - thin-film, 189
- platinum (Pt) resistors, 186
- platinum resistors, 196
  - class A, 196
  - tolerances class A, 197
- Poisson equation, 95
- polling, 351
- polymers, 65
- position sensitive detector, 69
- Power Spectrum VI module, 315
- power-down, 47
- power-down modes, 348
- Prandtl number, 154
- protection circuit, 298
- PSD, 69
- pseudo noise, 291
- psychrometer, 170
- PTAT
  - current source, 204
  - temperature sensor, 203
- PTAT-voltage generator
  - DEM, 206
- pulse-width modulation, 290, 344, 353
- PWM, 344, 353
- QEP, 369
- quadrature encoder pulse, 369
- quantization error, 291, 318
- quantization noise, 121, 291
- quantum efficiency, 80
- quasi-digital sensors, 313
- radiation
  - infrared, 154
- radiation properties, 79
- radio frequency identification, 360
- random errors, 33
- random-sampling method, 324
- real-time operation systems, 374
- reduced instruction set, 345
- relaxation oscillator, 245
- resistance
  - parasitic, 27
- resistive heating, 164
- resistor interface, 45
- responsivity, 79
- Reynolds number, 154
- RFID, 360
- RISC, 345, 355
- RMS converters, 172
- ROM, 346
- RTOS, 374
- Salmonella
  - infection, 29
  - Typhimurium, 29
- sampling error, 291
- saturation-current density, 105
- SAW, 74, 168

- scattering, 252
- scavenging
  - energy, 75
- Schmitt trigger, 210
- Seebeck coefficient
  - definition, 165
  - some values, 167
- Seebeck effect, 58, 59, 67
- selective detection, 238
  - selected parameters, 239
- self-calibration, 265
  - integrated coil, 265
- self-generating sensor, 4
- self-heating, 191, 192
- sensitivity
  - absolute, 254
  - current-related, 254
  - voltage-related, 255
- sensorization, 1
- short-term stability, 189
- shot noise, 105
- shunting conductance, 240
- sigma-delta converter, 294
- signal domains, 3, 58, 59
- silicon
  - bandgap, 82
- silicon sensors, 55
- smart car, 2, 16
- smart home, 2, 16
- smart sensor
  - definition, 9, 24, 61, 185
- smart sensor systems
  - definition, 11, 23
- smart temperature sensor, 208, 214
  - noise, 215
  - self heating, 216
  - SMT 160, 211
- smart temperature-sensor systems
  - with discrete elements, 212
- smart toys, 19
- SNR, 106
- SoC, 373
- solar cell, 88
- spinning-current, 269
- spinning-current technique, 260
- star-connected sensor system, 16
- Stefan-Boltzmann constant, 154
- Stokes approximation, 140
- SU-8, 134
- Surface-Acoustic-Wave (SAW) oscillator, 217
- surface acoustic waves, 74
- surface recombination velocity, 100
- synchronous detection, 34
- system clock, 349
- systematic errors, 33
- temperature sensors
  - accuracy, 189
  - dynamic behaviour, 194
  - heat leakage along wires, 194
  - noise and resolution, 190
  - requirements, 188
  - self-heating, 192
  - short-term and long-term stability, 189
- tandem transducers, 60
- TCD, 127
- temperature-sensing elements
  - Pt resistors, 187
  - thermistors, 187
  - thermocouples, 187
  - transistors, 187
- thermal accelerometers, 177
- thermal capacity, 157
- thermal conductivity detector, 127
- thermal cross-sensitivity, 256
- thermal model, 161
- thermal properties
  - conduction, 153
  - convection, 153
  - phase transition, 154
  - radiation, 154
- thermal resistance, 156
- thermal sensors
  - conduction, 153
  - convection, 153
  - phase-transition, 153
  - radiation, 153
- thermal-conductance sensors, 151, 152
- thermal-conductivity gauge, 176
- thermal-power sensors, 151

- thermal wind meter, 175
- thermistors, 187, 198
  - characteristics, 198
  - interface, 45
  - linearization, 199
- thermocouple, 165, 188, 305
- thermocouple-voltage processor, 305
- thermopiles, 165
- thick-film, 66
- thin-film, 66
- three-signal auto-calibration, 243
- three-signal measurement, 36
- throughput screening, 144
- time interval measurement, 352
- timer modules, 351
- transducers
  - active, 63
  - input, 56
  - modulating, 63
  - output, 56
  - passive, 63
  - self-generating, 63
- transistor temperature sensor, 188, 200
  - characteristics, 201
  - models, 201
  - PTAT sensor, 203
- transit time, 93
- transmission coefficient, 85
- trans-resistance circuit, 107
- triple point of water, 189
- two-port measurement, 27, 282
- UART, 355
- UFDC, 333
- undesired interaction
  - chemical effects, 297
  - electrical effects, 297
  - physical effects, 297
- Universal Frequency-to-Digital Converter, 333
- universal sensor interfaces, 51, 279
- universal transducer interface, 41
- UTI, 41, 300, 356, 366
  - nonlinearity, 49
  - resolution, 48
- UTI chip, 47
- UTI modes, 47
- vacuum sensor, 174
- virtual reality, 19-20
- virtual thermometer, 337
- voltage reference
  - intrinsic, 207
- von Neumann architecture, 345
- wave vectors, 83
- wind meter, 174
- wire impedance, 26
- yeast cell
  - detection, 137
- zener-zapping, 208, 209

<http://www.pbookshop.com>