

Contents

Preface	xiii
List of Acronyms	xv
1 Related Work and Preliminary Considerations	1
1.1 Introduction	1
1.2 Related Work	2
1.2.1 A Routing-Based Approach	2
1.2.2 An Information-Theoretic Approach	3
1.2.3 A Dynamic Control Approach	4
1.2.4 A Game-Theoretic Approach	4
1.3 A New Perspective for the Design of Ad Hoc Wireless Networks	5
1.4 Overview of the Underlying Assumptions in the Following Chapters	9
1.5 The Main Philosophy Behind the Book	11
2 A Communication-Theoretic Framework for Multi-hop Ad Hoc Wireless Networks: Ideal Scenario	15
2.1 Introduction	15
2.2 Preliminaries	16
2.2.1 Topology	16
2.2.2 Route Discovery	17
2.2.3 Average Number of Hops	18
2.3 Communication-Theoretic Basics	18
2.3.1 Bit Error Rate at the End of a Multi-hop Route	18
2.3.2 Link Signal-to-Noise Ratio	20
2.4 BER Performance Analysis	23
2.4.1 Uncoded Transmission	23
2.4.2 Coded Transmission	27
2.5 Network Behavior	29
2.5.1 Minimum Spatial Energy Density and Minimum Transmit Power for Full Connectivity	30
2.5.2 Connectivity: Average Sustainable Number of Hops	34
2.5.3 Lifetime of a Node	40
2.6 Concluding Remarks	41

3	A Communication-Theoretic Framework for Multi-hop Ad Hoc Wireless Networks: Realistic Scenario	43
3.1	Introduction	43
3.2	Preliminaries	44
3.3	Communication-Theoretic Basics	46
3.4	Inter-node Interference	48
3.4.1	Geometric Considerations	48
3.4.2	Traffic Model	49
3.5	RESGO MAC Protocol	50
3.5.1	Scenario with Strong LOS and Interference from Nodes in Tier 1	50
3.5.2	Scenario with Strong LOS and Interference from Nodes in Tiers 1 and 2	57
3.5.3	Scenario with Strong Multipath (Rayleigh Fading)	58
3.5.4	Discussion	63
3.6	RESLIGO MAC Protocol	64
3.6.1	Scenario with Strong LOS	66
3.6.2	Scenario with Strong Multipath (Rayleigh Fading)	69
3.6.3	Discussion	72
3.7	Network Behavior	73
3.7.1	Minimum Spatial Energy Density and Minimum Transmit Power for Full Connectivity	73
3.7.2	Scenario with Strong LOS	73
3.7.3	Scenario with Strong Multipath (Rayleigh Fading)	75
3.7.4	Connectivity: Average Sustainable Number of Hops	78
3.8	Conclusions	83
4	Connectivity in Ad Hoc Wireless Networks: A Physical Layer Perspective	85
4.1	Introduction	85
4.2	Quasi-regular Topology	86
4.2.1	A Formal Definition of Quasi-regular Topology	87
4.2.2	A Communication-Theoretic Approach	88
4.2.3	What Happens if Each Node has Two Spatial Neighbors?	93
4.2.4	What Happens if There is Inter-node Interference?	96
4.3	Random Topology	100
4.3.1	Related Work	100
4.3.2	Connectivity in Ad Hoc Wireless Networks with Random Topology	102
4.3.3	Evaluation of the Likelihood of Broadcast Percolation	104
4.3.4	What Happens if There is Inter-node Interference?	108
4.4	Concluding Remarks and Discussion	109
5	Effective Transport Capacity in Ad Hoc Wireless Networks	111
5.1	Introduction	111
5.2	Model and Assumptions	113
5.3	Preliminaries	115
5.3.1	Route Bit Error Rate	115
5.3.2	Link Signal-to-Noise Ratio	115
5.3.3	Average Sustainable Number of Hops	117
5.4	Single-Route Effective Transport Capacity	117

5.5	Aggregate Effective Transport Capacity	120
5.5.1	Ideal (no INI) Case	121
5.5.2	Realistic (INI) Case: RESGO MAC Protocol	123
5.5.3	Realistic (INI) Case: RESLIGO MAC Protocol	128
5.6	Comparison of the RESGO and RESLIGO MAC Protocols	131
5.7	Spread-RESGO: Improved RESGO MAC Protocol with Per-route Spreading Codes	134
5.8	Discussion	138
5.9	Concluding Remarks	141
6	Impact of Mobility on the Performance of Multi-hop Ad Hoc Wireless Networks	143
6.1	Introduction	143
6.2	Preliminaries	144
6.2.1	Ideal (no INI) Case	147
6.2.2	Realistic (INI) Case	147
6.3	Switching Models	149
6.3.1	Opportunistic Non-reservation-Based Switching	149
6.3.2	Reservation-Based Switching	150
6.4	Mobility Models	150
6.4.1	Direction-Persistent Mobility Model	150
6.4.2	Direction-Non-persistent (DNP) Mobility Model	155
6.5	Numerical Results	157
6.5.1	Direction-Persistent Mobility Model	157
6.5.2	Direction-Non-persistent Mobility Model	161
6.6	Conclusions	163
7	Route Reservation in Ad Hoc Wireless Networks	167
7.1	Introduction	167
7.2	Related Work	168
7.3	Network Models and Assumptions	169
7.3.1	Network Topology	169
7.3.2	Typical Routes	170
7.3.3	Bit Error Rate at the End of a Multi-hop Route	170
7.3.4	Retransmission Model	172
7.3.5	Mobility	172
7.4	The Two Switching Schemes	173
7.4.1	Reservation-Based Switching	173
7.4.2	Non-reservation-Based Switching	175
7.5	Analysis of the Two Switching Techniques	176
7.5.1	Reservation-Based Switching	176
7.5.2	Non-reservation-Based Switching	179
7.6	Results and Discussion	182
7.6.1	Switching Scheme and Traffic Load	182
7.6.2	Effects of Interference	183
7.6.3	Effects of the Number of Simultaneously Active Disjoint Routes	188
7.6.4	Effects of Node Spatial Density	189

7.6.5	Effects of Mobility	191
7.6.6	Implications on Practical Scenarios	192
7.7	Concluding Remarks	193
8	Optimal Common Transmit Power for Ad Hoc Wireless Networks	195
8.1	Introduction	195
8.2	Model and Assumptions	196
8.2.1	Network Topology	196
8.2.2	Routing	197
8.2.3	Medium Access Control Protocol	199
8.3	Connectivity	199
8.3.1	Square Grid Topology	200
8.3.2	Two-Dimensional Poisson Topology	201
8.4	BER at the End of a Multi-hop Route	202
8.4.1	Square Grid Topology	202
8.4.2	Random Topology	204
8.5	Optimal Common Transmit Power	204
8.5.1	Optimal Common Transmit Power for Networks with Square Grid Topology	204
8.5.2	Optimal Common Transmit Power for Networks with Random Topology	205
8.6	Performance Metrics	205
8.6.1	Node and Network Lifetime	205
8.6.2	Effective Transport Capacity	206
8.7	Results and Discussion	208
8.7.1	Optimal Transmit Power and Data Rate	208
8.7.2	Optimal Transmit Power and Node Spatial Density	210
8.7.3	Effects of Strong Propagation Path Loss	211
8.7.4	Connectivity Robustness to Node Spatial Density Changes	213
8.7.5	Practical Determination of the Optimal Transmit Power	215
8.8	Related Work	216
8.9	Conclusions	217
9	The Routing Problem in Ad Hoc Wireless Networks: A Cross-Layer Perspective	219
9.1	Introduction	219
9.2	Experimental Evidence	220
9.3	Preliminaries: Analytical Models and Assumptions	221
9.3.1	Physical Layer	221
9.3.2	Medium Access Control	225
9.3.3	Basic Networking Assumptions	226
9.4	Route Selection: Simulation Study	227
9.4.1	Network Topology	227
9.4.2	BER-Based Routing versus Shortest-Path Routing	227
9.5	Network Performance Evaluation	235
9.5.1	Average Hop Length Models	235
9.5.2	Retransmission Model	239

- 9.5.3 Packet Error Rate 239
- 9.5.4 Delay 240
- 9.6 Discussion 243
 - 9.6.1 Cross-layer Routing: A Practical Perspective 243
 - 9.6.2 Mobility 246
- 9.7 Related Work 246
- 9.8 Conclusions 248

- 10 Concluding Remarks 249**
 - 10.1 Introduction 249
 - 10.2 Extensions of the Theoretical Framework: Open Problems 249
 - 10.2.1 Performance of Ad Hoc Wireless Networks: Random Versus Uniform Topologies 249
 - 10.2.2 Impact of Clustering on the BER Performance in Ad Hoc Wireless Networks 251
 - 10.2.3 Impact of Receiver Sensitivity on the Performance of Ad Hoc Wireless Networks 253
 - 10.2.4 Spectral Efficiency–Connectivity Tradeoff in Ad Hoc Wireless Networks 254
 - 10.2.5 MIMO-OFDM Wireless Communications 256
 - 10.2.6 Smart Antennas and Directional Antennas 256
 - 10.3 Network Architectures 256
 - 10.4 Network Application Architectures 257
 - 10.5 Standards 258
 - 10.6 Applications 263
 - 10.7 Conclusions 264

- Appendix A Analysis of the Inter-node Interference 265**
 - A.1 Introduction 265
 - A.2 Exact Computation of the Average Link BER in a Scenario with Strong LOS 265
 - A.2.1 Interference from Nodes in Tier 1 266
 - A.2.2 Interference from Nodes in Tiers 1 and 2 271
 - A.2.3 Interference from Nodes in Tier 2 273
 - A.2.4 Simulation Scenario 274
 - A.3 Exact Computation of the Average Link BER in a Scenario with Strong Multipath (Rayleigh Fading) 276
 - A.3.1 Interference from Nodes in Tier 1 277
 - A.3.2 Interference from Nodes in Tiers 1 and 2 278
 - A.3.3 Interference from Nodes in Tiers 1, 2 and 3 278
 - A.4 LOS and Multipath (Rice Fading) 280
 - A.5 Gaussian Assumption for the Interference Noise 280
 - A.5.1 Route Bit Error Rate 282
 - A.5.2 Interference Power 284

- Appendix B Proof of Theorem 1, Chapter 5 287**

- Appendix C Route Discovery 293**

Appendix D	Validation of Analytical Results	295
D.1	Validation of Network Goodput	295
D.2	Validation of Delay	295
D.3	Validation of Average Number of Simultaneously Active Routes	297
Appendix E	Derivation of Joint CDF of W and Φ	299
References		307
Index		327

<http://www.pbookshop.com>