

# INDEX

After a page number, the letter 'e' means a significant equation, 'f' means a figure, 't' means a table. The index does not list every mention of a term. The Nomenclature and References are not indexed.

A		Bernoulli's equation	188–189
A-arm	14f	Bilstein	33f
absorber, resonant	86	bimetallic strip compensator	238f–239f
absorbing of shocks	1	Bingham flow	212, 318f, 397–400
acceleration sensitive valves	240, 244f	Bond number	187e
adaptive dampers	42, 296–301	BSA Telefork	40f
adjustable dampers	20, 33f, 289	bubble rising speed	188e
adjustable, electric	33f	shape	187
adjustables, rotary	250–253f	distinguishing diameter	187e
aerodynamic ride stiffness	125	size, <i>N</i> molecules	179
air suspension	31f, 32f	surface tension pressure	179
properties	375–378	velocity coefficient	188
aircraft oleo damper	241f	bubbles, appearance in liquid	181, 187
Andre Telecontrol	11f	bump camber coefficient, struts	153
Andre–Hartford scissor	5f	wishbones	153
Andrex oil bath	7f, 8f	bushes, <i>see also</i> mountings	
annular area of piston	269, 315e	amplitude effect	71
anti-roll bar stiffness factor	94–95	asymmetrical	44–45f
Arcton damper	180f	C	
area coefficient	204, 291, 293f, 295	Campbell	32f
Armstrong double telescopic	15f, 20f	cavitation	274–276
lever arm	18f	characteristic equation, damped	103
asymmetry of force	129e	undamped	97
automatic valves/dampers	295–299	Chrysler Oriflow damper	262f
axle vibrations	122	Citroen air suspension	31f
inclined dampers	167f	coil inductance	329
B		Colebrook diagram	194f
Belleville washer stack	222	Colebrook's equation	194e
bellows valve	252	colloidal ferrofluids	216
bend losses in pipe	200	compliance in series, <i>see also</i>	
		series stiffness	43

- compressibility effects 276–278  
 related to acceleration 277–278  
 compression velocity 260  
 configurations of damper 17–33  
 continuity, principle of 188  
 continuous velocity pick off 356  
 cost effectiveness of active valve 296  
 of damper specified 335  
 Coulomb damping 74–77  
 on ride height 76  
 damping 74–77  
 friction 15  
 creeping motion 268  
 cubic equation solution 386–389  
 CVP 356  
 cyclical characteristics 278–282f
- D
- damper characteristics, main  
 parameters 259  
 matching, of pairs 357  
 model, polynomial 141  
 models in ride 88  
 listed 88  
 optimisation 129–132  
 specification, listed 333  
 damping asymmetry 126, 131–134  
 coefficient  $C$  66e, 67  
 coefficient required 67, 126  
 factor  $\alpha$  66e, 67  
 ratio  $\zeta$  67, 68e  
 from motion trace 68e  
 optimum 67  
 DampMatic 249  
 Darcy–Weisbach equation 193e  
 data processing in testing 347–348  
 de Carbon telescopic 25f  
 de Guzmán-Carrancio 174e  
 Delco ride levelling 35f  
 Delco-Lovejoy 22  
 diameter specified 334  
 diffuser 202  
 loss factor  $\varepsilon$  202  
 recovery coefficient  $\zeta_R$  203  
 disc valve 219f, 220f  
 discharge coefficient  $C_d$  203–207  
 as  $K$  205  
 with cavitation 206e  
 discomfort loop 128f
- passenger 111, 112f, 113  
 tyre 111–116  
 displays of  $F(V)$  curve 261f  
 double piston 288f  
 telescopic 15f, 16f  
 wishbones 150–153  
 double-acting shim valve 249, 251f  
 double-tube damper 23f, 24f, 27f, 28f, 29f, 30f  
 drop test 47, 48t  
 drowned efflux 206e  
 dual path mounting 46f, 47f  
 durability testing 338, 357  
 dynamic index, pitch 91  
 pressure 192
- E
- Einstein's equation 175e  
 electromagnetic damper 31, 35f  
 electromechanical testers 342  
 electrorheological, *see also* ER  
 electrorheological fluids 214t–216  
 elliptic springs 1, 5f  
 emulsification 179–184  
 emulsified oil damper 26f  
 emulsion 179–186  
 compressibility 185f, 186e  
 density 181–184, 182e, 183f  
 viscosity 186e  
 end fittings specified 334  
 frequencies 88–89  
 energy dissipated per cycle 349  
 entry losses 200f  
 equivalent linear damping  
 coefficient 263  
 mass (compressibility) 278  
 ER controlled valve 319, 320f  
 ER damper 314–319  
 capacitance 318e  
 design 314f  
 fast switching 319f  
 fibrous microstructure 313  
 fluid properties 311  
 material model 314f  
 materials 309–314  
 mechanism of viscosity  
 change 312  
 stick slip 313f  
 evolution of damper, stages 1–2  
 exit losses 203

- expansion number (bubble) 187e  
 extension limiter, hydraulic 40f  
 velocity of damper 260f
- F
- fade 172, 239, 276  
 failure speeds 52  
 fast adaptive dampers 289  
 FBD of piston 270f  
 floating secondary piston 248f  
 fluid momentum 189–191  
 foam 180  
 force cancellation by resonance 351  
 forced vortex 210  
 force-momentum analysis of valve 190  
 force-velocity curve specified 334  
 Foster snubber 4  
 free body diagram of piston 270f  
 free vortex 210, 211f, 212e  
 frequency domain ride analysis 117  
 frequency ratio 71e  
 of highest  $T$  73  
 sensitive valves 245  
 selective damping 249  
 friction force 268e  
 types, listed 15  
 mechanical 265  
 piston, rod, seal 265, 266  
 strut 266, 267  
 front girder fork 159f  
 leading link 158f  
 trailing link 157f  
 froth 180  
 FSD 249  
 Fuchs 17, 21  
 Fukushima 52, 129f–131f, 246, 247f
- G
- Gabriel snubber 7f  
 gas absorbability in oil 177e  
 gas absorption coefficient  $C_{GA}$  178  
 volume coefficient  $C_{GLV}$  182  
 bulk modulus 177  
 compressibility 177  
 density 176e  
 force 268e, 269e  
 springing 19  
 stiffness 269e  
 viscosity 176e
- general damper configuration 271  
 Girling Arcton damper 180  
 Greeves dry friction 6f  
 Guzmán-Carrancio 174e
- H
- Hadamard 188  
 Hagen-Poiseuille equation 193e, 254, 255  
 handling qualities of vehicle 120  
 straight line 120–121  
 $Q_H$  124–128  
 Hartford 3, 4, 5f, 6f  
 Telecontrol 4, 6f  
 head valve 257  
 heave and pitch undamped 2-dof 95  
 damped, 1-dof 92  
 undamped, 1-dof 90  
 model parameters 112f  
 with link compliance 139f  
 heave-and-pitch damped 2-dof 102–104  
 roll analysis 102–104  
 damped 2-dof simplified 100–102  
 damped 2-dof, characteristic equation 103  
 Heaviside D-operator 65, 96, 102  
 Henry's equation 177e  
 Houdaille rotary vane 9f, 10f  
 human tolerance to vibration 115ef  
 Hydragas 20, 32f  
 hydraulic dampers, success factors 9, 11, 15  
 diameter 195  
 testers 344  
 Hydrolastic 20, 32f  
 Hydromat (Boge) 37f
- I
- induced velocity of vortex 210f, 211e  
 inlet edge radius, effect on losses 200e, 206  
 instantaneous stroke 246f  
 instrumentation for testing 345  
 in-use thickening (MR) 323  
 iron pentacarbonyl 321  
 ISO 2631 115  
 IUT 323
- J
- jacking force 286–287

- K
- Kendall's equation 175e
- Kinchin and Stock 17f–22f, 43f–45f, 55
- Kindl 55, 244f
- kinematic viscosity 173e, 377e
- kinetic energy correction factor 198t, 315e
- knee of  $F(V)$  curve 12, 140e, 228f, 232
- Komamura and Mizumukai 19f, 242f, 243f, 248f, 253f–254f
- Koni 27f
- L
- Lancia Lambda pillar 12f
- LDE 323
- leaf spring friction 3f
- springs 3f, 5f, 11
- length range specified 334
- lever arm, parallel piston 19f, 169
- single acting 21f
- life of damper specified 335
- lifetime dissipated energy 323
- liquid expansion compensator 239f
- solid suspensions 212–214
- literature review 54–60
- loading function for tolerance 115e
- Lovejoy hydraulic 12, 13f, 22f
- Lucas parallel piston 13f, 19f
- Luvax rotary vane 18f
- M
- magnetorheological, *see also* MR
- magnetorheological fluids 59, 214–216, 321–324
- magnification factor 70
- Mannesman Sachs levelling 38f, 39f
- manufacture 53
- mass (load) variation 63
- maximum area of valve 291, 292f, 294
- mean damping coefficient 259, 263e
- power dissipation 349, 350f
- mechanical friction 265–268
- minor losses 199
- modal damping coefficient 101e
- factor 101e
- ratio 101e
- frequencies 97e
- inertia 100e
- positions 99e, 100e
- stiffness 101e
- mode shapes 98e
- momentum correction factor 99f, 198t
- of fluid 189–191
- Moody diagram 194f
- Moody's equation 194e
- motion ratio adjustment of damping 301
- displacement method 137–138
- effect 139–142, 141f
- installation 301
- scaling effect 142t
- motorcycle front suspensions 156–160
- rear suspensions 160–165
- mountings, *see also* bushes
- mountings 42–47
- MR damper coefficient 329
- design 324f, 330f, 331f
- analysis 327t
- complete model 332f
- magnetic circuit 325f
- fluid properties *v.* solid content 322t
- properties 322t
- materials 214–216, 321–324
- multi stage valve 257
- N
- Nikuradse 197
- Nivomat (Boge) 37f
- noise 287
- O
- oil additives 171
- compressibility 172e
- density 171e
- properties 170t
- listed 171
- specified 335
- surface tension 179
- thermal capacity 175
- conductivity 176
- expansion 172e
- vapour pressure 176e
- viscosity 173–175
- causes of 173
- temperature effect 174e
- on-road testing 357
- operating range 130f
- operating temperature range 170
- optimum suspension damping 82, 124–128

- stiffness 125  
 orifice flow 203–207, 204f  
 orifices, combined 207–209  
   parallel 207, 208f  
   series 207, 208f  
   triple 208, 209f  
 Oriflow damper 262f
- P**
- parallel hole 290, 291f, 294  
   piston damper 13f, 19f  
 passenger on seat 118–119  
   effect on vehicle 119  
 passenger-tyre discomfort loop 128f  
 peak velocity pick off 356  
 Penske racing damper sections 358f, 359f  
 Peterson 23, 55  
 piezoelectric valves 249, 250f  
 pipe flow 191  
   regime laminar/turbulent 192f  
   Reynolds number 191e, 192e  
   noncircular sections 195–196  
     friction factor  $f$  194f  
     laminar pressure loss 193e  
     laminar/turbulent transition 194  
     turbulent pressure loss 192e  
     velocity profiles 196–199  
 piston and rod forces, listed 269  
   mass 270  
   seals 54  
 pitch vibration 121  
 Poisson's ratio 283–284  
 position sensitive valves 240, 242f  
 position-dependent dampers 35, 240–243  
 Prandtl 197, 377e  
 pressure loss coeff  $K$  as  $C_d$  205  
 pressure-rate valves 243–245f  
 pressures and forces 272–273  
 production quantity 1  
 progressivity factor 259, 264e  
 pullrods 155  
 purging 337  
 pushrods 155  
 PVP 356
- Q**
- quartic characteristic equation 103  
 quadratic damping 77–79  
   equation solution 65, 385–386
- quality factor (ER & MR) 215  
 quarter car model (repudiated) 111  
   *see* heave model  
 quartic equation solution 103e, 389–391
- R**
- Rabinow patent abstract 305  
 range of a damper 53  
 ratio of damping ratios, heave and pitch 93  
   frequencies, heave and pitch 90, 92  
 relative roughness 194  
 remote valve systems 42f  
 resistance reducing with length 205  
 resonant absorber 86–87  
 ride motions 49–50  
   quality  $Q_R$  122  
 ride-handling compromise 121, 124–128  
   parameter  $f_{SR}$  126, 127e  
   quality loop 125f, 126f  
 ride-levelling 33–35  
 rigid arm suspension 148–150  
   listed types 148  
 rim impact event 133  
 rising rate factor 144e, 147e  
 RMQ of Gaussian distribution 116  
 RMS of Gaussian distribution 116  
 road modelling 105–110  
   roughness, correlation of tracks 109–110  
   ISO model 106, 107f  
   reference spectral density 108t  
   spectral 106–110  
   sinusoidal 106  
   testing categories list 338  
 rocker design 142–148, 143f–145f  
   deviation angle 145e  
 rod valve 219f, 221, 222f  
 roll centre height, struts 155  
   height, wishbones 153  
 roll vibration 121  
   damped 94–95  
   undamped 93–94  
 rotary adjustables 250–252, 253f
- S**
- safety certification 338  
 scalogram 288f  
 scissor action discs 3, 4f, 5f, 6f

- damper 129f
- Scotch yoke 343f
- seat, vibration isolating 118f
- selection tables, high/low
- damping 300t
- semi-active dampers 289
- series hole 290, 291f, 294
- stiffness 79–85
- settlement velocity 214e
- shim valve 223–225, 223f, 224f
- bending modes 224f
- double acting 249–250, 251f
- SI units 393–395
- sink rate on dampers 105e
- sinusoidal test theory 348–351
- sliding forks 156f
- pillar 12f
- slow adaptive dampers 289, 299
- snubber 4, 7f
- solenoid actuator 251f
- solution of equations 385–391
- spatial frequency, road
- resonant 106e
- specific damping coefficient 68
- stiffness 67
- Speckhart and Harrison 56, 240, 244f
- speed, operating 47–53
- spool valve 219f, 222f–223
- F–M analysis 190
- Stabilus anti-roll system 22f
- steering dampers 21, 34f
- static damper forces 268
- steering damper 5f
- problems 124
- vibrations 124
- Stokes' equation 187e, 214
- strain analysis 283–286
- effect on cylinder
- volume 286
- negative axial 284
- stress analysis 283–286
- stroke, free and installed 135
- sensitive valves 245–249
- utilisation 135
- operating 47–53, 52t, 53f
- strut side forces 266, 267f
- suspension 153–155
- low motion ratio 154
- front 29f, 30f
- top mounting 46f, 47f
- sudden contraction 201f
- expansion 201f
- supersaturated solution
- gas-in-oil 179
- surface roughness 194t
- suspension workspace 114
- liquid–solid 212–214
- Sutherland's equation 177e
- T
- Telecontrol 4, 6f, 11f
- Telefork 35, 40f
- telescopic damper, basic types 34f
- conventional 23f, 24f
- general form 37–42, 41f
- standard 24f
- temperature compensation for fade 237–239
- effect 276
- rise in testing 349
- test procedure 352t, 352–354
- sheets 381–383
- testing categorisation list 337
- thermal expansion of materials 172, 237
- Thompson 128
- time domain ride analysis 113–117
- timetable, early development 7
- transfer factor 131e, 259, 264e
- transient response traces 339–341
- testing 338–342
- transients, acceleration 50
- roll 51
- transmissibility factor 69e, 70f, 71e, 72ef
- greatest 73
- peak 73, 73t, 74f
- road to passenger 117f
- triangular test 354–356
- Truffault 3, 4f, 5f
- tube valve 252, 255f
- U
- ultrasonic ride height measurement 57, 297f
- units (SI) and conversions 393–395
- V
- valve area coefficient 291–295
- characteristics listed 225–227
- flow rates 271–272

- force–momentum analysis 190f  
 fully closed pressure 291, 293f, 294  
 fully open pressure 291  
 power dissipation 227e  
 switching speed 298  
 types listed 219–220, 219f  
   adjustable 290–294  
   area fraction open 233  
   variation with  $P$  228  
 basic models 227–230  
 bellows 252  
 general model 231–233  
 in head 257  
 knee 232  
 linear analysis 273–274  
 multi-stage 257  
 piezoelectric 249, 250f  
 simple area analysis 218et  
 solution of flow rate 235–237  
   stages 232, 233f  
 transition pressure ratio 234e  
   region 233  
 volumetric flow ratio 234  
 variable stiffness 295f  
   vortex 209–212, 246–249  
 valves in pistons 20f  
 vane damper, double acting 9i  
 vapour pressure 176, 274, 275  
 variable hole 291  
   stiffness valve 295f  
 vehicle ride damping coefficients,  
    $C_{D0}$  etc. 102e  
   stiffness coefficients  $C_{K0}$  etc. 96e, 102e  
 velocities and forces 260, 261f  
 velocity coefficient 188e, 204  
   profile reciprocal index 197  
   *vena contracta* 201f, 204f  
 vibration, forced damped, 1-dof 71–74  
   undamped, 1-dof 68–71  
   free damped, 1-dof 63–68  
   2-dof 85–86  
   undamped, 1-dof 61–63  
   2-dof 85  
 viscosity of a mixture 175e  
   of a suspension 175e  
   kinematic 173e  
 von Karman 197  
 vortex 209–212  
   radial pressure gradient 211  
   strength 211  
   valve 246, 247f, 248f, 249  
  
 W  
   wall forces 285f  
   wallowing 67  
   Walther viscosity equation 175e  
   water, properties 379–380  
   wear 67, 168  
   Weisbach 193  
   wheel hop 119–120  
   white noise test 356  
   Winslow patent abstract 304f, 307  
   wishbone suspension 14f, 150–153  
   Woodhead emulsified 26f  
   Woodhead–Monroe telescopic 16f  
  
 X, Y, Z  
   zeitgeist, historical 2

<http://www.pbookshop.com>