

Index

- accessibility 2.145, 3.26–3.32
- agricultural buildings 1.9
- air change rates 2.99, 2.100, 3.23–3.24
- air ducts, fire safety 2.87
- air permeability 3.6, 3.9–3.10
- air pressure testing 3.9–3.10
- air vents 2.129
 - see also* mechanical extract ventilation
- air-admittance valves 2.112
- alternating tread stairs 2.139–2.140
- ancient monuments 2.99, 2.141
- ancillary buildings 1.10
- Approved Documents 1.4
- approved inspectors 1.8
- asbestos 1.15, 5.13
- attached garages
 - doorways from domestic accommodation 2.27
 - electrical installations 2.149
 - typical plan layout 5.17, 5.30
 - see also* integral garages
- background ventilation 2.100, 3.23
- barn conversions 5.40–5.49
- basements 2.16–2.18
 - conversions 5.38–5.40
 - means of escape 2.85–2.86
 - ventilation 2.100
- bat protection 1.13
- bathrooms
 - design room temperature 2.124
 - electrical installations 2.148, 2.149
 - provision 2.101
 - ventilation 2.100, 3.24
- BBA (British Board of Agreement) 1.5
- beams *see* structural columns/beams
- below ground pipes 2.104, 2.106
- below ground structures *see* basements
- block paving 2.150
- blockwork *see* masonry
- boarding *see* weatherboarding
- boilers, hot water 2.124–2.125
- boundaries, fire protection distances 2.91
- breathable buildings 5.13, 6.3–6.4
- breathable paints 6.12
- breather membranes
 - pitched roofs 2.68
 - timber-framed walls 2.44, 2.45
- brickwork *see* masonry
- British Board of Agreement (BBA) 1.5
- Building (Approved Inspectors etc.) Regulations 2010 1.8
- Building Act 1984 1.3
- building control approval 1.7–1.8
- building control notices 1.9
- building log book 2.145
- Building Notice application 1.7
- Building Regulations 2010 1.3
- buttressing walls 2.28–2.29, 2.30, 2.37
- carbon emission targets 3.4–3.5
- carbon monoxide alarms 2.129
- carports 1.10
- cavity barriers 2.35, 2.43
 - around windows 2.86
 - fire resistance 2.90
- cavity closers 2.35, 2.43, 2.49
 - basement conversions 5.40
 - flat roofs 2.75
 - party walls 2.55
- cavity spacers 2.35, 2.38
- cavity walls 2.35–2.41, 2.97
 - garage conversions 5.29–5.34
 - inspection 5.11
 - insulation 2.35, 2.37, 2.39–2.40, 2.98, 3.13
 - timber-framed walls 2.44, 2.45, 2.46, 3.14
 - loft conversions 4.5, 4.7
 - timber-framed 2.41–2.47, 3.14
 - see also* external walls
- CDM (Construction (Design and Management) Regulations) 2007 1.15
- ceiling joists 2.62, 2.63
 - notches/holes/cuts in 5.9
 - timber sizes 2.65

- ceilings 2.57
 - fire resistance 2.90
 - height 2.60
 - surface spread of flame 2.89
- cement mortars and renders 2.75–2.77
- certification 1.5
- cesspools 2.118–2.119
- change of use 5.5–5.6
- chimneys
 - fire protection 2.125, 2.131
 - flue block 2.130
 - heights 2.132
 - inspection and cleaning 2.130–2.131
 - loft conversions 4.4
 - masonry 2.125–2.126, 2.127
 - metal 2.129, 2.130, 2.131
 - providing restraint 2.32
 - see also* flues
- cladding
 - timber 2.41–2.43
 - timber-framed walls 2.45–2.46, 3.15
- clay heave protection 2.13, 2.14–2.15, 2.21–2.24
- clay paint 6.16
- clear protective coatings 6.16
- Code for Sustainable Homes 3.12, 3.15, 3.18
- cold water supplies 2.100–2.102, 2.143
- columns *see* structural columns/beams
- combined sewers 2.120, 2.124
- combustion air vents 2.100, 2.129, 2.132
- combustion appliances *see* gas heating appliances; oil heating appliances; solid fuel appliances
- commissioning certificates
 - combustion appliances 2.135
 - fixed building services 2.103, 2.144
 - gas heating appliances 2.133
 - hot-water storage 2.101
 - oil heating appliances 2.133
 - renewable energy systems 2.135
- compartment floors
 - fire resistance 2.90
 - openings 2.86
 - separating buildings 2.91
- compartment walls
 - fire resistance 2.90
 - lengths 2.28
 - minimum thickness 2.29–2.30, 2.32
 - openings 2.86
 - separating buildings 2.91
- Competent Person Schemes (CPS) 1.10–1.11
- concrete, frost protection 1.13–1.14
- concrete mixes 2.9–2.10
- concrete paths, etc. 2.149–2.150
- condensation risks 1.5–1.6, 2.18, 2.97
- consequential improvements 2.144
- conservation areas
 - energy conservation 2.141
 - planning consents 1.14
- conservation of fuel and power *see* energy performance
- Conservation of Habitats and Species Regulations 2010 1.13
- conservatories 1.10
- Construction (Design and Management) Regulations 2007 (CDM) 1.15
- consumer units
 - accessible 3.28
 - electrical installations 2.149
 - flood protection 2.147
- contaminants, resistance to 2.92–2.96
 - see also* radon protection
- contaminated materials/soil 1.15
- contravention of regulations 1.8
- Control of Asbestos Regulations 2012 1.15
- controls, accessible 3.28, 3.29
- conversions
 - barns 5.40–5.49
 - basements 5.38–5.40
 - feasibility 5.6–5.13
 - garages 5.16–5.38
 - lofts Section 4
 - material change of use 5.5–5.6
 - sound insulation 5.51–5.52
 - underpinning for 5.14–5.16
- corridor widths 3.27
- covered yards/ways 1.10
- CPS (Competent Person Schemes) 1.10–1.11
- cracking, masonry 5.7
- curtain walls, U values 3.6
- damp penetration 5.11, 6.3
- damp-proof course trays, etc. 2.96
- damp-proof courses (dpcs) 2.96, 5.11
- daylighting 3.5
- demolitions 1.12
- Design Emission Rate (DER) 3.6
- disabled access 2.145, 3.26–3.32
- discharge pipes from safety devices 2.102, 3.24–3.25
- discharge stacks 2.110, 2.111, 2.112
- doors
 - accessibility 3.27
 - fire-resisting 2.83, 4.13–4.15
 - safety glazing 2.146, 2.147
 - U values 2.142, 3.6
 - see also* external doors; internal doors
- dormer roofs 2.69
 - loft conversions 4.6, 4.9–4.10
 - U values 2.144
- double glazing, U values 2.142, 3.7
- drain trenches 2.106–2.107
- drainage *see* foul-water drainage; rainwater drainage
- drainage fields 2.115, 2.117
- drainage mounds 2.115
- draught-proofing 2.142, 3.8
- drives 2.149–2.150
- Dwelling Emission Rate (DER) 3.5

- electrical installations 2.147–2.149
- electrical water heating 2.102
- elements of structure, fire resistance 2.89, 2.90
- emergency escape *see* means of escape
- emulsion paint 6.16
- energy performance
 - additional requirements 1.4–1.5
 - conversions 5.13, 5.53
 - domestic extensions 2.141–2.145
 - new buildings 3.4–3.19
 - operating information 3.10
 - see also* thermal insulation
- Energy Performance Certificates (EPC) 3.5, 5.53
- energy-efficient lighting 2.143, 3.9
- entrance doors, accessibility 3.27
- escape doors 2.85
- escape from building *see* means of escape
- escape stairs 2.86–2.87, 2.88
 - loft conversions 4.15–4.16
 - see also* protected stairways
- escape windows 2.85, 2.99, 4.12–4.13
- exempt buildings and work 1.9–1.10
- extensions Section 2
 - cavity wall insulation 2.97–2.98
 - combustion appliances 2.124–2.133
 - conservation of fuel and power 2.141–2.145
 - disabled access 2.145
 - drainage 2.103–2.124
 - electrical safety 2.147–2.150
 - fire safety and means of escape 2.78–2.92
 - fuel storage 2.134
 - glazing safety 2.146
 - intermediate upper floors 2.56–2.60
 - internal partitions 2.56
 - mortars, renders and gypsum plasters 2.75–2.76
 - protection from falling, collision and impact 2.135–2.140
 - renewable energy 2.134–2.135
 - resistance to contaminants 2.92–2.96
 - resistance to moisture 2.96–2.97
 - roofs
 - flat 2.70–2.75
 - pitched 2.60–2.70
 - sanitation 2.100–2.103
 - separating walls and floors 2.53–2.55
 - sound insulation 2.98–2.99
 - sub-structure 2.9–2.27
 - superstructure 2.28–2.53
 - ventilation 2.99–2.100
 - water supply 2.100–2.103
- external boarding *see* weatherboarding
- external doors
 - accessibility 3.27
 - closing around 2.141–2.142, 3.8
 - means of escape 2.85
 - opening widths 3.27
 - sealing and draught-proofing 3.8
 - thresholds 3.27
 - U values 2.142, 3.6
- external lighting 3.9
- external paths, etc. 2.149–2.150
- external sheathing 2.41–2.43
- external stairs
 - accessible 3.26–3.27
 - fire exits 2.86–2.87, 2.88, 4.15–4.16
 - guarding and landings 2.138–2.139
- external walls 2.28–2.53
 - barn conversions 5.43–5.44, 5.48, 5.49–5.51
 - cavity walls *see* cavity walls
 - defective 5.7
 - fire resistance 2.86–2.87, 2.88, 2.89, 2.90
 - garage conversions 5.21–5.26
 - insulation 2.44, 2.45–2.46, 3.13–3.15
 - lateral restraint 2.28–2.29
 - loft conversions 4.5, 4.7
 - minimum thickness 2.29–2.30, 2.32
 - sizes and proportions 2.28
 - solid masonry *see* solid masonry walls
 - timber-framed *see* timber-framed walls
 - U values 2.144, 3.6
 - see also* cavity walls
- extract ventilation *see* mechanical extract ventilation
- fire detection and alarm systems 2.78
- fire exits *see* means of escape
- fire resistance
 - cavity barriers 2.90
 - ceilings 2.57, 2.90
 - compartment floors 2.90
 - compartment walls 2.90
 - elements of structure 2.89, 2.90
 - external walls 2.86–2.87, 2.88, 2.89, 2.90
 - lift shafts 2.90
 - load-bearing walls 2.90
 - party floors 2.91
 - party walls 2.53, 2.54–2.55, 2.91
 - protected stairways 2.90
 - roofs 2.90
 - separating floors 2.53–2.54, 2.90
 - separating walls 2.90
 - structural columns/beams 2.90
 - and thermal insulation 2.43
 - upper floors 2.84, 2.90
- fire separation 2.83
 - between an integral garage and dwelling 2.86, 2.87
 - loft conversions 4.15–4.16
- fire-fighting vehicle access 3.19
- fireplaces 2.125
 - flues 2.130
 - minimum air gap and wall thickness 2.43–2.44
- fire-resisting construction 2.83–2.84, 2.86
 - see also* cavity closers; protected stairways
- fire-resisting doors 2.83, 4.13–4.15
- flame spread, internal linings 2.89

- flat roofs
 - with cold deck 2.70–2.72
 - coverings 2.70–2.71
 - garage conversions 5.19–5.20
 - green roofs 2.74
 - insulation 2.72, 2.73, 2.145
 - timber sizes 2.76
 - U values 2.144
 - with warm deck 2.72–2.74
 - coverings 2.72, 2.74
 - inverted 2.74
 - workmanship 2.75
- floating floors 2.24–2.25
- flood protection 2.97, 2.147
- floor areas 1.10, 2.28
- floor joists 2.56–2.58
 - conversions 5.8
 - notches/holes/cuts in 5.9
 - strapping to walls 2.49–2.51
- floor screed 2.23, 5.26–5.28, 5.35–5.36, 5.48–5.49
- floorboards 2.57–2.58
- floors
 - sound insulation 2.98
 - thermal insulation 2.21–2.27, 2.145
 - U values 2.144, 3.6, 3.11–3.12
 - see also* ground floors; upper floors
- flues
 - configuration 2.127, 2.130
 - connecting pipes 2.129
 - heights 2.132
 - inspection and cleaning 2.130–2.131
 - liners 2.125–2.126
 - minimum air gap and wall thickness 2.42–2.43, 2.125, 2.128
 - notice plates 2.133
 - repair/relining 2.132–2.133
 - sizes 2.131
 - see also* chimneys
- foul-water disposal 2.108–2.113, 5.12
- foul-water drainage 2.103–2.108, 5.12
- foundations 2.9–2.16
 - clay heave protection 2.13–2.15
 - concrete mixes 2.9–2.10
 - conversions 5.7
 - underpinning 5.14–5.16
- frost protection 2.143
- fuel storage tanks 2.134
- Full Plans application 1.7

- gable-end walls 2.51
- galleries, means of escape 2.85
- galletting 6.8
- garages 1.10
 - conversions
 - cavity wall 5.29–5.34
 - single wall 5.16–5.29
 - electrical installations 2.149
 - external walls 2.47
 - fire separation 2.86
 - floor slope 2.86
 - ground-bearing concrete floors 2.27
 - separating walls 2.37, 2.41
 - sizes and proportions 2.47, 2.48
- garden sheds 1.10
- gardens 2.149–2.150
- gas heating appliances 2.133, 3.6
- Gas Safe 2.133
- glazing
 - double and triple 2.142, 3.7
 - on escape routes 2.84
 - insulation 2.141–2.142
 - protected stairways 4.14, 4.15
 - total area of 2.141, 3.22
 - U values 2.142, 3.6, 3.7
 - see also* windows
- gravel paths 2.150
- green roofs 2.74
- greenhouses 1.9
- grey water harvesting 2.120
- ground floors 2.19–2.27
 - conversions 5.7–5.8
 - barn conversions 5.45–5.51
 - garage conversions 5.26–5.29, 5.34–5.38
 - insulation 2.21–2.27, 3.11–3.12
- ground-bearing solid concrete floors 2.20–2.21
 - conversions 5.8, 5.36–5.37, 5.46–5.48
- guarding, stairs, etc. 2.136–2.137, 2.138–2.139, 3.28
- gullies 2.106
- gypsum plasters 2.77

- haired lime plaster 6.12
- handrails 2.136, 2.137, 2.138, 2.140, 3.27
- headroom 2.60
 - loft conversions 4.4
 - stairs 2.135, 2.139–2.140
- Health and Safety at Work etc. Act 1974 (HSWA) 1.15
- hearths
 - notice plates 2.133
 - open fireplaces 2.125
 - solid-fuel stoves 2.127, 2.128
- heat alarms 2.78
- heating appliances *see* hot-water systems; space heating appliances
- height of building 2.28
- height of ceilings *see* headroom
- height of storeys 2.28, 2.29
- hot water supplies 2.100–2.102
- hot-water safety 3.24
- hot-water storage 2.101
- hot-water systems 2.124–2.125
 - insulation 2.125, 2.143
 - thermal efficiency 3.6
- hydraulic lime 6.11–6.12

- insect attack 5.10
 inspection chambers 2.106, 2.108, 2.109
 insulation *see* sound insulation; thermal insulation
 integral garages
 fire separation 2.86, 2.87, 2.90
 radon protection 2.27
 see also attached garages
 intermediate upper floors *see* upper floors
 internal doors
 air gap 3.22
 fire-resisting 2.83, 4.13–4.15
 internal lighting 2.143, 3.9
 internal load-bearing walls
 loft conversions 4.11
 minimum thickness 2.30, 2.56
 internal partitions 2.56
 internal stairs 2.135–2.138
 minimum width 3.27
 see also protected stairways
 internal walls
 sound insulation 2.98, 3.21, 5.52
 surface spread of flame 2.89
 intumescent paint/paper system 2.83

 Japanese knotweed 1.14
 joist hangers/caps 2.57

 kitchens
 design room temperature 2.124
 electrical installations 2.148
 ventilation 3.24

 lamps, energy-efficient 2.143, 3.9
 landfill gas 2.96
 landings 2.136, 2.137, 3.27
 lateral restraint 2.28–2.29
 roofs to walls 2.51–2.52
 upper floors to walls 2.49–2.51
 walls at ceiling level 2.52–2.53
 lead paint 1.15
 lean-to roof abutment 2.62–2.63, 2.70
 Lifetime Homes 3.31–3.32
 lift shafts, fire resistance 2.90
 light wells 2.68
 lighting, energy-efficient 2.143, 3.9
 lime, compressive strength 6.15
 lime mortars, renders and plasters 6.5–6.8,
 6.10–6.12
 lime putty 6.10–6.11
 lime techniques Section 6
 limewash 6.12, 6.15–6.16
 lintels 2.48
 cavity walls 2.35, 2.37, 2.43
 defective 5.7
 listed buildings
 conversions 5.51
 energy conservation 2.141
 planning consents 1.14
 sound insulation 3.20
 load-bearing walls, fire resistance 2.90
 local authority building control 1.7
 lofts
 conversions Section 4
 feasibility 4.3–4.4
 fire safety and means of escape 4.11–4.16
 structure 4.5–4.11
 fixed ladders 2.140
 hatches, doors and light wells 2.69
 stairs to 2.139
 LPG storage tanks 2.134

 maintenance of old buildings Section 6
 manholes 2.109
 manual controls 3.28, 3.29
 masonry
 chimneys 2.125–2.126, 2.127
 compressive strength 2.32–2.34
 cracking 5.7
 external walls
 external skin to timber-framed walls 2.42–2.43
 inspection 5.11
 loft conversions 4.7
 internal partitions 2.56
 maximum height of building 2.28
 maximum wall lengths 2.28
 minimum thickness 2.29–2.30, 2.32
 movement joints 2.49
 natural stone-faced cavity walls 2.35–2.37, 2.38
 party walls 2.53–2.54, 2.55
 see also solid masonry walls
 masonry paint 6.16
 material change of use 5.5–5.6
 materials and workmanship 1.5
 means of escape 2.79–2.86
 basements 2.85–2.86
 loft conversions 4.4, 4.11–4.16
 mechanical extract ventilation 2.99–2.100, 3.22, 3.24
 interaction with heating appliances 2.131, 2.133
 metal chimneys 2.129, 2.130
 metallic roof trims 2.75
 methane protection 2.96
 micro generation systems 2.134
 mineral-based wall paints 6.16
 moisture penetration 5.11, 6.3
 mortars
 analysis 6.6
 lime-based 6.5–6.8
 movement joints
 masonry 2.49
 pipework 2.107

 natural emulsion paints 6.16
 natural hydraulic lime (NHL) 6.11–6.12
 natural lighting 3.5

- natural stone-faced cavity walls 2.35–2.37, 2.38
 natural ventilation 2.99, 3.21–3.22
 new dwellings Section 3
 cavity wall insulation 3.20
 combustion appliances 3.26
 conservation of fuel and power 3.4–3.19
 disabled access 3.26–3.32
 drainage 3.25–3.26
 electrical safety 3.32
 fire safety and means of escape 3.19
 fuel storage 3.26
 glazing safety 3.32
 hot-water safety 3.24–3.25
 protection from falling, collision and impact 3.26
 resistance to contaminants 3.20
 resistance to moisture 3.20
 sanitation 3.24–3.25
 sound insulation 3.20–3.21
 ventilation 3.21–3.24
 waste disposal 3.25–3.26
 water efficiency 3.25
 non-hydraulic lime 6.10–6.11
 non-traditional construction 5.10
 Northern Ireland
 building regulations 1.3
 Lifetime Homes 3.32

 oil heating appliances 2.133
 oil storage tanks 2.134
 oil/fuel separators 2.121–2.122
 open fireplaces 2.125
 flues 2.130
 ventilation 2.132
 opening up existing structure 1.13, 4.5
 openings
 cavity walls 2.37
 closing around 3.8
 fire protection 2.90
 sealing 3.8
 trimmed joists 2.58, 2.59
 ventilation 2.99, 3.22, 3.23
 OSB (orientated strand board) 2.41
 outbuildings 1.10

 paints 6.16–6.17
 lead 1.15
 party floors
 conversions 5.51–5.52
 fire resistance 2.91
 sound insulation 2.98
 Party Wall Act 1996 1.15–1.17
 party walls 2.53
 conversions 5.51–5.52
 fire resistance 2.91
 sound insulation 2.98, 3.20, 5.9–5.10
 U values 3.6, 3.7
 passageway widths 3.27
 passenger lifts, fire safety 2.86

 PassivHaus standard 3.18–3.19
 paths 2.149–2.150
 patios 2.149–2.150
 paved areas 2.150
 percolation tests 2.116–2.117
 photovoltaic panels 3.9–3.10
 piers 2.28–2.29, 2.32
 piled foundations 2.16
 pipework
 drainage 2.104–2.106
 insulation 2.102–2.103, 2.143
 movement joints 2.107
 penetrating through walls 2.105, 2.142, 3.8, 3.9
 see also waste pipes
 pitched roofs 2.60–2.69
 barn conversions 5.41–5.43
 coverings 2.61
 cut roof construction 2.62
 garage conversions 5.14–5.19, 5.29–5.32
 insulation 2.65–2.68, 2.145, 3.11, 3.12
 loft conversions 4.6, 4.9
 roof trusses 2.62
 structure 2.62–2.69
 timber sizes 2.62, 2.64–2.65, 2.66
 U values 2.144
 underlay and undersheeting 2.61
 valleys and lead work 2.68
 ventilation 2.66
 planning permission 1.14
 plasters
 lime-based 6.5–6.6, 6.9–6.10, 6.12, 6.13–6.15
 repairs 6.9–6.10
 porches 1.10
 pozzolanic materials 6.12
 precast concrete slabs 2.150
 preliminary works 1.11–1.14
 pressure testing 3.9–3.10
 private sewers, transfer arrangements 1.12, 2.122–2.123
 private water supplies 2.101
 professional advice 1.6
 protected stairways 2.81–2.82, 2.83–2.84
 fire resistance 2.90
 loft conversions 4.13–4.15
 protection of the works 1.13–1.14
 protective coatings 6.16–6.17
 public sewers 1.12
 building over or close to 2.122–2.123
 connections to 2.120, 2.123
 pumped drainage 2.101, 2.112–2.113
 purge ventilation 2.99, 3.21–3.22

 radiator valves 2.124
 radon protection 2.19, 2.20, 2.21, 2.93–2.95, 5.10
 raft foundations 2.13, 2.16
 rainwater disposal 2.120–2.121
 rainwater down pipes 2.119
 rainwater drainage 2.104, 2.119–2.122, 2.150
 rainwater gutters 2.119

- rainwater harvesting 2.120
- ramps 2.140, 3.26, 3.29
- recesses
- cavity walls 2.37
 - fireplace walls 2.135
- reed-bed systems 2.115–2.116
- refuse storage 3.26
- Regularisation certificates 1.7
- renders 2.75–2.77
- analysis 6.6
 - lime-based 6.5–6.6, 6.9–6.10, 6.12, 6.13–6.15
 - repairs 6.9–6.10
 - timber-framed walls 2.44, 2.45, 3.15
- renewable energy systems 2.134
- replacement windows, fire safety 2.86
- repointing 6.6–6.8
- retaining walls 2.16–2.17
- Rights of Light 1.17–1.18
- rising damp 5.11, 5.48, 6.3
- roof pitch 2.63
- roof trusses 4, 2.62, 4.3
- roof underlay 2.61
- roof valleys 2.68, 2.70
- roof windows, U values 2.142, 3.6
- roofs
- conversions 5.8–5.9
 - garage conversions 5.16–5.20
 - loft conversions 4.3–4.4, 4.5–4.10
 - coverings 2.91, 2.92, 5.9
 - fire resistance 2.90
 - insulation 3.12, 3.16–3.17
 - strapping to walls 2.51–2.52
 - U values 2.144, 3.6, 3.16–3.17
 - ventilation 3.12, 5.12
 - see also* dormer roofs; flat roofs; pitched roofs
- room temperatures 2.124
- safety glazing 2.146, 2.147
- sanitary pipework 2.108, 2.111
- sanitary rooms *see* bathrooms; WCs
- SAP (Standard Assessment Procedure) 3.4
- Scotland, building regulations 1.3
- sealing
- openings 2.142, 3.8, 3.9
 - service penetrations 2.105, 2.142, 3.8, 3.9
- separating floors
- fire resistance 2.53–2.54, 2.90
 - garages 2.90
 - sound insulation 3.20, 5.9–5.10
- separating walls 2.53–2.56
- fire resistance 2.90
 - garages 2.37, 2.41, 2.90
 - lengths 2.28
 - minimum thickness 2.29–2.30, 2.32
 - see also* party walls
- septic tanks 2.113–2.114
- service penetrations, sealing 2.142, 3.8, 3.9
- sewage pump sets 2.113
- sewage treatment systems 2.114–2.119
- sewers *see* private sewers; public sewers
- sheds 1.10
- silicate paint 6.16
- site assessment 1.11–1.12
- small detached buildings 1.10
- smoke alarms 2.78
- smoke testing 2.113
- soak-aways 2.121
- sockets, accessible 3.28, 3.29
- soil types, foundations 2.11, 2.13
- soil-and-vent pipes (SVP) 2.60, 2.110, 2.111
- solar heat gain 3.5, 3.8
- solar pv 3.9–3.10
- solar water heating 2.102
- solid fuel appliances 2.125–2.133
- air supply 2.129, 2.132
 - free-standing stoves 2.126–2.129
 - interaction with extract ventilation 2.131
- solid masonry walls
- barn conversions 5.43–5.45
 - inspection 5.11, 6.5
 - insulation 2.40, 2.145, 3.14
 - lime-based methods 6.5–6.10
 - loft conversions 4.7–4.8
 - repair/rebuilding 6.8–6.9
- solid waste storage 2.124
- sound insulation 2.98–2.99, 3.20–3.21
- floor voids 2.57
 - party walls 2.53, 2.54–2.55
 - conversions 5.9–5.10, 5.51–5.52
 - upgrading 2.55
 - timber stud partitions 2.56
- sound testing 2.55, 2.98, 5.52
- space heating appliances 2.124–2.133
- thermal efficiency 3.6
- sprinkler systems 2.87–2.89, 3.19
- loft conversions 4.16
- stages of works, notices 1.9
- stairs *see* external stairs; internal stairs
- Standard Assessment Procedure (SAP) 3.4
- statutory service authorities 1.12
- stepped foundations 2.12
- stone slabs 2.150
- stone-faced cavity walls 2.35–2.37, 2.38
- storey heights 2.28, 2.29
- storm-water drainage 2.104
- strapping 2.49–2.53
- strip foundations 2.10–2.11
- structural columns/beams 2.41, 2.48
- defective 5.7
 - fire resistance 2.90
- structural timber 1.13
- moisture content 2.75
 - notches/holes/cuts in 2.41, 2.59, 5.9
 - treatment 2.75
- stub stacks 2.112
- sub-structure walls 2.18–2.19, 5.47, 5.49

- Supply (Water Fittings) Regulations 1999 2.103
- surface coatings 6.16–6.17
- surface finish, paths, etc. 2.150
- surface spread of flame 2.89
- surface water disposal 2.120–2.121, 5.12
- surface water drainage 2.120, 2.150, 5.12
- suspended beam-and-block ground floors 2.22–2.24, 3.12
- suspended reinforced in-situ concrete ground floor slabs 2.21–2.22, 3.11
- suspended timber ground floors 2.25–2.27
 - garage conversions 5.37–5.38
- sustainable homes 1.5, 3.12, 3.15, 3.18
- swimming pool basins 2.144
- switches, accessible 3.28, 3.29

- tanking systems 2.18, 2.97, 5.11–5.12
 - barn conversions 5.47, 5.48
 - basement conversions 5.39–5.40
 - garage conversions 5.25
- Target Emission Rate (TER) 3.4
- tarmac areas 2.150
- temperature control 2.124
- temporary buildings 1.10
- thermal bridging 3.6, 3.8
- thermal insulation
 - closing around window and door openings 2.141–2.142, 3.8
 - cold water supplies 2.143
 - condensation risks 1.5–1.6
 - and fire resistance 2.43
 - floors 2.21–2.27, 2.60, 2.145, 3.11–3.12
 - floating floors 2.24–2.25
 - ground-bearing floor slabs 2.21
 - suspended beam-and-block ground floors 2.23–2.24
 - suspended reinforced in-situ concrete ground floor slabs 2.22
 - upper 2.60, 3.11, 3.15
 - hot-water systems 2.125, 2.143
 - loft conversions 4.5–4.10
 - pipework 2.102–2.103, 2.143
 - roofs 3.11, 3.16–3.17
 - cold deck flat roofs 2.70, 2.72, 2.145
 - dormer 4.9–4.10
 - pitched roofs 2.65–2.68, 3.11
 - warm deck flat roofs 2.72, 2.73
 - upgrading 2.144–2.145, 6.7
 - walls
 - cavity 2.35, 2.37, 2.39–2.40, 2.44, 2.97–2.98
 - external in new buildings 3.11, 3.15
 - between heated and unheated areas 2.37, 2.41, 3.14
 - solid masonry 2.40, 2.145, 3.14, 4.7–4.8, 6.7
 - timber-framed 2.44, 2.46, 3.14–3.15, 4.12
 - water tanks/cisterns 2.143
 - see also* U values
- thermal mass 3.6

- third-party-accredited certification 1.5
- timber cladding 2.41–2.42
- timber decay 5.10
- timber stud partitions 2.56
- timber-framed construction 2.41, 5.10
- timber-framed walls 2.41–2.47
 - cladding 2.44, 2.47
 - fire safety 2.43–2.44
 - insulation 3.14–3.15, 4.12
 - loft conversions 4.11
 - party walls 2.54–2.55
 - renders 2.44, 2.45
 - U values 3.14–3.15, 4.12
- timber-sizing tables 1.6
- toilets *see* WCs
- trees, heave protection 2.12, 2.14–2.15
- trench-fill foundations 2.11–2.13
- trimmer/trimming joists 2.58, 2.59
- triple glazing, U values 3.7
- trussed roofs 2.62, 4.3
- tundish 2.102, 3.24–3.25
- twin-walled metal chimneys 2.129, 2.130

- U values
 - doors 2.142, 3.6
 - floors 2.144, 3.6
 - exposed upper 3.15
 - garage conversions 5.45
 - ground 3.11–3.12
 - glazing 2.142, 3.6, 3.7
 - roof lights 3.6
 - roofs 2.144, 3.6, 3.16–3.17
 - garage conversions 5.16, 5.19, 5.29, 5.33, 5.42–5.45
 - swimming-pool basins 2.144
 - walls
 - cavity 3.13, 3.14, 4.5–4.6, 4.8, 5.33–5.34
 - curtain walling 3.6
 - external 2.144, 3.6, 3.15
 - garage conversions 5.33–5.34
 - between heated and unheated areas 3.14
 - loft conversions 4.5, 4.7, 4.8, 4.12
 - party walls 3.6, 3.7
 - solid masonry 4.7, 4.8, 5.43
 - timber-framed walls 3.14–3.15, 4.12
 - windows 2.142, 3.6
- under-floor heating systems 2.24
- underground pipes 2.104, 2.106
- underpinning 5.14–5.16
- unvented hot-water storage 2.101
- upgrading
 - sound insulation 2.55
 - thermal insulation 2.144–2.145, 6.7
- upper floors 2.56–2.60, 2.61
 - conversions 5.8, 5.43–5.45
 - fire resistance 2.84, 2.90
 - insulation 2.60, 3.15

- lateral restraint 2.49
- means of escape 2.84
- sound insulation 5.52
- thermal insulation 3.11
- see also* lofts, conversions
- uPVC
 - cladding 2.45–2.46
 - pipework 2.86, 2.104, 2.110
 - soffits, fascias and barge boards, etc. 2.62
- urea–formaldehyde (UF) 2.98
- utility companies 1.12

- vapour-control barrier 2.75
- vapour-permeable membranes *see* breather membranes
- vented hot-water storage 2.101
- ventilation 2.99–2.100, 3.21–3.24
 - garage conversions 5.12, 5.42–5.43
 - to heating appliances 2.100, 2.129, 2.132
 - loft conversions 4.4
 - roofs 3.11
- ventilation ducts, fire safety 2.87
- ventilation rates 2.100, 3.23–3.24
- vertical lateral restraint 2.28–2.29

- Wales
 - building regulations 1.3
 - conservation of fuel and power 1.5
 - Lifetime Homes 3.32
 - planning requirements 3.15
 - sprinkler systems 3.19
- wall plates 2.52
- wall ties 2.35, 2.36, 2.43, 2.49
- wall tiling 2.45
- walls
 - abutments 2.47
 - defective 5.7
 - between heated and unheated areas 2.37, 2.41, 3.14
 - heights and lengths 2.28, 2.31, 2.32
 - lateral restraint 2.28–2.29
 - U values 3.6
 - see also* external walls; internal walls; party walls
 - waste pipes 2.108–2.112
 - waste storage 3.25–3.26
 - waste traps 2.108, 2.110
 - waste water treatment 2.113
 - water efficiency 3.25
 - water heating *see* hot-water systems
 - water supply service pipes 2.103
 - water tanks/cisterns 2.101
 - insulation 2.103, 2.143
 - WCs 2.101
 - accessible 3.29–3.30
 - design room temperature 2.124
 - ground floor 3.29
 - ventilation 3.22
 - weatherboarding 2.41, 2.45, 2.46
 - see also* cladding
 - weep holes 2.48
 - wet rooms
 - ventilation 2.100, 3.22, 3.23
 - see also* bathrooms; kitchens; WCs
 - wetland drainage treatment 2.115–2.116
 - wheelchair access 3.27–3.30
 - wholesome water supply 2.100–2.101
 - Wildlife and Countryside Act 1981 1.13
 - windows
 - closing around 2.141–2.142, 3.8
 - energy conservation 2.141–2.142
 - guarding 2.139
 - maximum area of 2.141, 3.22
 - means of escape 2.85, 2.99, 3.22, 4.12–4.13
 - sealing and draught-proofing 2.142, 3.8
 - U values 2.142, 3.6
 - ventilation 2.99, 3.21–3.22
 - see also* glazing
 - work stages, notices 1.9
 - workmanship *see* materials and workmanship
 - workshops 1.10